

DATASHEET QUICK'UP+ R



GENERAL

| Art.Nr: | H-328 | Net weight: | 0.22 kg |
|------------------------|---------------|---------------|---------|
| GTIN: | 8057733302392 | Gross weight: | 0.22 kg |
| Customs tariff number: | 76169990 | | |



DATASHEET

QUICK'UP+ R

Right-hand light alloy ascender handle with ergonomic rubber grip for climbing ropes.

Main features:

- overmolded, ergonomic handle ascender, designed for greater efficiency when pulling and increased resistence to wear and tear:
- cam opening lever usable with one hand; patented system for unlocking the cam, with just one downwards movement necessary;
- steel cam, manufactured with technology that implements the resistance to wear and tear. Equipped with a set of teeth that protects the wear of the rope, but it is equally effective in blocking and ascending the rope. It also has three slots to prevent the accumulation of mud and reduce the effort needed to slide the device up the rope under any condition (muddy rope, frozen etc.);
 two attachment holes for various possible
- two attachment noies for various possible uses, anti-inversion cam system, secondary hole for connecting a maglia rapide for an etrier.

FEATURES

| FEATURES | | |
|-----------------------------------|----------------|--|
| Colour: | Orange, Black | |
| Minimum compatible rope diameter: | 10.00 mm | |
| Maximum compatible rope diameter: | 13.00 mm | |
| Minimum temperature: | -35 °C | |
| Maximum temperature: | 45 °C | |
| UIAA compliance: | Yes | |
| Working Load Limit: | 140 kg | |
| Patent status: | Patented | |
| Hot forged: | No | |
| Hard coated: | No | |
| Ascender type: | hand_ascenders | |
| DIMENSIONS | | |
| Minimum rope diameter / EN 12841: | 10 mm | |
| Maximum rope diameter / EN 12841: | 13 mm | |
| Minimum rope diameter / EN 567: | 0 mm | |
| Maximum rope diameter / EN 567: | 0 mm | |
| Maximum rope diameter / EN 12278: | 0 mm | |
| Product length: | 18.30 cm | |
| B 1 1 1 1111 | 0.00 | |

MATERIAL

Product width:

Material: Aluminium

9.30 cm