

DATASHEET

ROLLNLOCK



GENERAL

Art.Nr:	H-336	Standards:	EN 12278:2007, EN 12841:2006/B, EN 567:2013
GTIN:	8057733309599	Net weight:	0.09 kg
Customs tariff number:	76169990	Gross weight:	0.09 kg

DATASHEET

ROLLNLOCK

Ultra-light multi-function device for rope access work and rescue. Compact and easy to handle, it has three different modes of operation: ascender, pulley or progress-capture hauling pulley.

Main features:

- the new design and the different colours of the side plates make using it even more intuitive;
- it allows ascending the rope in accordance with EN 567 / EN 12841-B standards (ascender mode);
- thanks to the ability of locking the cam, it can be used as a simple pulley for lifting or transferring a load in accordance with the EN 12278 standard (pulley mode);
- it allows the direct lifting of a load, the creation of hauling systems and the rescue or self-rescue of a person (progress-capture hauling pulley mode);
- when used in pulley mode, the rope is free to run in both directions; instead, when the hauling-pulley mode is used, the rope can only run in one direction and it is locked in the opposite one;
- switching from one mode to another is intuitive and it can even be done with gloves on or while operating in difficult conditions;
- its compact size and light weight make it an ideal companion to carry on the harness at all times, for any eventuality.
- Caution! This equipment is not a fall arrester (EN 353-2 / EN 12841-A) nor can it be used for self-belaying while climbing.

FEATURES

Colour: Orange, Anthracite

Maximum lifetime: 30 years

Minimum temperature: -30 °C

Maximum temperature: 40 °C

Ascender type: hand_ascenders

DIMENSIONS

Minimum rope diameter / EN 12841: 10 mm

Maximum rope diameter / EN 12841: 13 mm

Minimum rope diameter / EN 567: 8 mm

Maximum rope diameter / EN 567: 13 mm

Maximum rope diameter / EN 12278: 13 mm

MATERIAL

Material: Aluminium