

DATASHEET

SKYSAFE PRO FLEX Y



GENERAL

Art.Nr:	L-0623-1,8
GTIN:	4030281202523
E-class number:	40-21-08-10
Customs tariff number:	56090000

Standards:	ANSI Z359.13-6/12FTFF:2013,EN 354:2010,EN 355:2002,EN 795:2012/B,MEETS CSA Z259.11-05-E6:2010,RFU PPE-R/11.063,RFU PPE-R/11.074
------------	---

Net weight:	2.68 kg
Gross weight:	2.68 kg

DATASHEET

SKYSAFE PRO FLEX Y

ONE4ALL - The SKYSAFE PRO Revolutionary, new, patented energy absorber with the large weight range from 50 - 140kg (110 - 310 lbs.) that always withstands a maximum impact of less than 6 kN at a maximum absorber length of 1.75m (5.7 Feet). The final impact resistance of 22 kN, also in the absorber, before AND after a fall is exceptional as well. SKYSAFE PRO furthermore meets the most relevant international standards in one SINGLE product. UNIQUE: The built-in, adjustable RESCUE LOOPS! As a result, rescuers need not set up a rescue system and hereby save precious time in a rescue! Available in four versions with different carabiner combinations: I-web, Y-web, I-web tie-back, Y-web tie-back.

FEATURES

Colour:	Orange, Black, Grey
---------	---------------------

Fallindicator:	Yes
----------------	-----

Impact force:	6.00 kN
---------------	---------

Hand wash:	40 °C
------------	-------

Edge approved:	Yes
----------------	-----

Maximum lifetime:	10 years
-------------------	----------

Minimum tensile strength:	22.00 kN
---------------------------	----------

Minimum temperature:	-35 °C
----------------------	--------

Maximum temperature:	45 °C
----------------------	-------

Rescue loop:	Yes
--------------	-----

Lanyard type:	Y-Version
---------------	-----------

DIMENSIONS

length_lanyard:	1.80 m
-----------------	--------

Lanyard rope diameter:	30.00 mm
------------------------	----------

MATERIAL

Material:	Polyester, Aluminium, Steel
-----------	-----------------------------